

CARUS REMEDATION

CAS Registry No. 10101-50-5
EINECS No. 233-251-1

RemOx® L ISCO Reagent

FACT SHEET



RemOx® L ISCO reagent has been specifically manufactured for environmental applications such as remediation of soils and associated groundwater. This product can be used to degrade a variety of contaminants including chlorinated solvents, polyaromatic hydrocarbons, phenolics, organo-pesticides, and substituted aromatics. RemOx L is shipped with a certificate of analysis to document assay, pH, and trace metals.

PRODUCT SPECIFICATIONS

Assay

39.5-41.0% as NaMnO_4

pH

5.0-8.0

Trace Metals

(see Table I)

CHEMICAL/PHYSICAL DATA

Formula	NaMnO_4
Formula Weight	141.93 g/mol
Appearance	Dark Purple Solution
Specific Gravity	1.365-1.385 g/mL
Freezing Point	-15° C/ 5° F
Solubility in Water	Miscible with water in all proportions.
Material will pass through a 10 micron filter.	

APPLICATIONS

RemOx L is used for soil and groundwater remediation by *in situ* or *ex situ* chemical oxidation and as an active agent in subsurface reactive barriers for treatment of: chlorinated ethenes, phenolic compounds, polyaromatic hydrocarbons, RDX, HMX, and various pesticides.

SHIPPING CONTAINERS

5-gallon pail (20-L) (UN Specification: UN3H1/Y1.8/100) Made of high-density polyethylene (HDPE), weighs 3.5 lbs (1.6 kg). The net weight is 57 lbs (25.9 kg). The pail stands approximately 14.8 in (37.6 cm) tall, 10.6 in (26.9 cm) wide, and 11.0 in (27.9 cm) deep. (Domestic and international)

55-gallon drum (208-L) (UN Specification: UN1H1/Y1.4/100) Made of high-density polyethylene (HDPE), weighs 22 lbs (10 kg). The net weight is 550 lbs (250 kg). The drum stands approximately 34.8 in (88.3 cm) tall, has an outside diameter of 23.3 in (59.1 cm). (Domestic and international)

SHIPPING CONTAINERS

275-gallon IBC (Intermediate Bulk Container) (1040-L) (UN Specification: UN31HA1/Y1.9/100) They are also marked "MX" for multi-trip. IBC weighs 139 lbs (65 kg). The net weight is 3000 lbs (1360 kg). The IBC contains 263 gallons (1000 L) of product. The IBC dimensions are 45.4 in (115.3 cm) high, 48 in (121.9 cm) long, and 40 in (101.6 cm) wide. The IBC has a 2 in (5 cm) butterfly valve with NPT threads in bottom sump. (Domestic)

275-gallon IBC (Intermediate Bulk Container) (1040-L) (UN Specification: UN31HA1/Y1.9/100) They are also marked "MX" for multi-trip. IBC weighs 132.5 lbs (60 kg). The net weight is 3000 lbs (1360 kg). The IBC contains 263 gallons (1000 L) of product. The IBC dimensions are 45.8 in (116.2 cm) high, 39.4 in (100.0 cm) long, and 47.3 in (120.0 cm) wide. The IBC has a 2 in (5 cm) butterfly valve with NPT threads in bottom sump. (International)

Bulk Shipping- Quantities up to 4000-gallons (15,142-L) are available. (Domestic only)

HANDLING, STORAGE, AND INCOMPATIBILITY

Like any strong oxidizer RemOx L should be handled with care. Protective equipment during handling should include face shields and/or goggles, rubber or plastic gloves, and rubber or plastic apron. If clothing becomes spotted, wash off immediately; spontaneous ignition can occur with cloth or paper. In cases where significant exposure exists use the appropriate NIOSH-MSHA dust or mist respirator.

Store in accordance with NFPA 30 requirements in the United States or the European Fire Protection Association in Europe for Class II oxidizers. Additional regulations in Europe are REACH (Regulation for Registration, Evaluation, Authorisation and Restriction of Chemicals), and CLP (Classification, Labeling, Packaging). REACH is a regulation that increases the responsibility of the industry to manage the risks that the chemical may pose. For REACH registration numbers refer to the eSDS. The product should be stored in a cool, dry area in closed containers. Concrete floors are preferred. Check local regulations to ensure proper storage. Avoid wooden decks. Spillage should be collected and disposed of properly. To clean up spills and leaks follow the steps recommended in our MSDS or eSDS.

Avoid contact with acids, peroxides, and all combustible organic or readily oxidizable materials including inorganic oxidizable materials and metal powders. With hydrochloric acid, chlorine gas is liberated. RemOx L is not combustible, but will support combustion. It may decompose if exposed to intense heat. Fires may be controlled and extinguished by using large quantities of water. Refer to the MSDS or eSDS for more information.

CARUS CORPORATION

CORPORATE HEADQUARTERS | 315 Fifth Street, Peru IL 61354 | Tel + 1.815.223.1500 / 1-800-435-6856 | Fax + 1.815.224.6697 | Web: www.caruschem.com | E-Mail: salesmkt@caruschem.com
CARUS EUROPE | Parque Empresarial de ASIPO | C/Secundino Rocas 3, Planta 1, Oficina 13-14 | 33428 Cayes, Llanera Spain | Tel + 34.985.78.55.13 / Fax + 34.985.78.55.10
CARUS WATER, JINING | Jiangmiao Village, Ershilipu Town, Rencheng District, Jining City, | Shandong Province, China. 272000 | Tel + 86.053.7279.1228 / Fax + 86.053.7279.1339

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change; and the conditions of handling, use or misuse of the product are beyond our control. Carus Corporation makes no warranty, either expressed or implied, including any warranties of merchantability and fitness for a particular purpose. Carus also disclaims all liability for reliance on the completeness or confirming accuracy of any information included herein. Users should satisfy themselves that they are aware of all current data relevant to their particular use(s).

Carus and Design is a registered service mark of Carus Corporation. RemOx® is a registered trademark of Carus Corporation. Responsible Care® is a registered service mark of the American Chemistry Council.



RESPONSIBLE CARE®
OUR COMMITMENT TO SUSTAINABILITY

ONE COMPANY. ENDLESS SOLUTIONS

Copyright 2007
rev. 01/13
form RX 1603

CARUS®



RemOx® L ISCO reagent is classified as an oxidizer for both domestic and international transportation. Liquid permanganate is shipped domestically as Freight Class 70 and in E.U. as Class 5.1.

Proper Shipping Name: Permanganates, inorganic, aqueous solution n.o.s. (contains sodium permanganate).

Hazard Class: Oxidizer, Class 5.1

Identification Number: UN 3214

Division/APR/RID Class: 5.1

Label Requirements: Oxidizer, 5.1

Packaging Group: II

Packaging Requirements: 49 CFR Parts 171 to 180

Sections: 173.152, 173.202, 173.242

Quantity Limitations:

1 liter net for passenger aircraft or railcar:

5 liters net for cargo aircraft.

Vessel Stowage, (IMDG Regulation):

D-material must be stowed "on-deck" on a cargo vessel, but is prohibited on a passenger vessel. Other provisions: stow separately from ammonium compounds, hydrogen peroxide, peroxides, super-oxides, cyanide compounds, and powdered metal.

H.S. Code 28.41.69.00

SHIPPING CONTAINERS

RemOx L is compatible with many metals and synthetic materials. Natural rubbers and fibers are often incompatible. Solution pH and temperature are also important factors. The material selected for use with liquid permanganate must be compatible with any kind of acid or alkali being used.

In neutral and alkaline solutions, RemOx L is not corrosive to carbon steel and 316 stainless steel. However, chloride corrosion of metals may be accelerated when an oxidant such as liquid permanganate is present in solution. Plastics such as Teflon, polypropylene, and HDPE are also compatible with liquid permanganate.

Aluminum, zinc, copper, lead, and alloys containing these metals may be (slightly) affected by RemOx L. Actual corrosion or compatibility studies should be made under the conditions in which RemOx L will be used.

Table I: Typical Trace Metal Content and Specifications

Element	Typical Analysis (mg/kg)	Specifications (mg/kg)	DL* (mg/kg)	Element	Typical Analysis (mg/kg)	Specifications (mg/kg)	DL* (mg/kg)
Ag	BDL	0.15	0.034	Fe	BDL	2.00	0.053
Al	BDL	2.00	0.24	Hg	BDL	0.03	0.003
As	BDL	4.00	0.006	Ni	BDL	0.1	0.03
Ba	2.96	15.00	0.016	Pb	BDL	0.70	0.16
Be	BDL	0.50	0.08	Sb	BDL	0.70	0.16
Cd	BDL	0.10	0.016	Se	0.0034	0.50	0.0003
Cr	2.71	5.00	0.031	Tl	BDL	3.50	0.80
Cu	BDL	0.10	0.022	Zn	0.034	0.40	0.011

DL* is detection limit

BDL is below detection limit